


DAISY-MINI-M

~30° wide beam

SPECIFICATION:

Dimensions	279.5 x 21.0 mm
Height	13.3 mm
Fastening	pin, screw, snaps
ROHS compliant	yes ⓘ

MATERIALS:




Component	Type	Material	Colour	Finish
F17029_DAISY-MINI-M	Linear lens	PMMA	clear	
F17667_DAISY-MINI-SHD-MET-MATT	Shade	PC	metal	matt
F17666_DAISY-MINI-SHD-MET	Shade	PC	metal	gloss
F17465_DAISY-MINI-SHD-WHT-MATT	Shade	PC	white	matt
F17034_DAISY-MINI-SHD-MATT	Shade	PC	black	matt
F17033_DAISY-MINI-SHD-WHT	Shade	PC	white	gloss
F17028_DAISY-MINI-SHD	Shade	PC	black	gloss

ORDERING INFORMATION:

Quantities for one set:

Linear lens	1
Shade	1

Component		Qty in box	MOQ	MPQ	Box weight (kg)
F17029_DAISY-MINI-M » Box size: 398 x 298 x 265 mm	Linear lens	252	252	12	5.8
F17034_DAISY-MINI-SHD-MATT » Box size: 398 x 298 x 265 mm	Shade	252	252	4	6.1
F17028_DAISY-MINI-SHD » Box size: 398 x 298 x 265 mm	Shade	252	252	4	5.9
F17465_DAISY-MINI-SHD-WHT-MATT » Box size: 398 x 298 x 265 mm	Shade	252	252	4	6.2
F17666_DAISY-MINI-SHD-MET » Box size: 398 x 298 x 265 mm	Shade	252	252	4	5.9
F17033_DAISY-MINI-SHD-WHT » Box size: 398 x 298 x 265 mm	Shade	252	252	4	5.9
F17667_DAISY-MINI-SHD-MET-MATT » Box size: 398 x 298 x 265 mm	Shade	252	252	4	6.2





See also our general installation guide: www.ledil.com/installation_guide



OPTICAL RESULTS (MEASURED):




LED J Series 2835
FWHM / FWTM 35.0° / 75.0°
Efficiency 85 %
Peak intensity 1.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:
F17667_DAISSY-MINI-SHD-MET-MATT



LED Opticus Daisy Mini M L28W2
FWHM / FWTM 34.0° / 68.0°
Efficiency 73 %
Peak intensity 1.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:
F17034_DAISSY-MINI-SHD-MATT




LED LinLED 280x20mm 1100lm 8x0 2C 42V Opt G1
FWHM / FWTM 58.0° / 87.0°
Efficiency 59 %
Peak intensity 0.6 cd/lm
LEDs/each optic 2
Light colour White
Required components:
F17028_DAISSY-MINI-SHD




OPTICAL RESULTS (SIMULATED):




LED XQ-E HI
FWHM / FWTM 34.0° / 75.0°
Efficiency 88 %
Peak intensity 1.8 cd/lm
LEDs/each optic 1
Light colour White
Required components:
F17666_DAISY-MINI-SHD-MET




LED XQ-E HI
FWHM / FWTM 32.0° / 72.0°
Efficiency 78 %
Peak intensity 1.8 cd/lm
LEDs/each optic 1
Light colour White
Required components:
F17034_DAISY-MINI-SHD-MATT



LED XQ-E HI
FWHM / FWTM 30.0° / 72.0°
Efficiency 80 %
Peak intensity 1.8 cd/lm
LEDs/each optic 1
Light colour White
Required components:
F17028_DAISY-MINI-SHD




LED LUXEON HL1Z
FWHM / FWTM 30.0° / 62.0°
Efficiency 86 %
Peak intensity 2.3 cd/lm
LEDs/each optic 1
Light colour White
Required components:
F17028_DAISY-MINI-SHD




OPTICAL RESULTS (SIMULATED):




LED NCSxE17A
FWHM / FWTM 30.0° / 62.0°
Efficiency 87 %
Peak intensity 2.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:
F17028_DAISY-MINI-SHD




LED NFSWE11A
FWHM / FWTM 34.0° / 68.0°
Efficiency 79 %
Peak intensity 1.7 cd/lm
LEDs/each optic 4
Light colour White
Required components:
F17028_DAISY-MINI-SHD



LED NFSWE11A
FWHM / FWTM 26.0° / 55.0°
Efficiency 89 %
Peak intensity 3 cd/lm
LEDs/each optic 1
Light colour White
Required components:
F17028_DAISY-MINI-SHD




LED Duris E 2835
FWHM / FWTM 26.0° / 62.0°
Efficiency 94 %
Peak intensity 2.8 cd/lm
LEDs/each optic 1
Light colour White
Required components:
F17028_DAISY-MINI-SHD



OPTICAL RESULTS (SIMULATED):


SAMSUNG

LED LM28xB Series
FWHM / FWTM 32.8° / 68.0°
Efficiency 82 %
Peak intensity 2 cd/lm
LEDs/each optic 1
Light colour White
Required components:
F17028_DAISY-MINI-SHD




SAMSUNG

LED LM302D
FWHM / FWTM 28.0° / 62.0°
Efficiency 91 %
Peak intensity 2.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:
F17465_DAISY-MINI-SHD-WHT-MATT




SAMSUNG

LED LM302D
FWHM / FWTM 28.0° / 62.0°
Efficiency 87 %
Peak intensity 2.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:
F17028_DAISY-MINI-SHD



SEOUL SEMICONDUCTOR

LED SEOUL 3030
FWHM / FWTM 26.0° / 60.0°
Efficiency 90 %
Peak intensity 2.9 cd/lm
LEDs/each optic 1
Light colour White
Required components:
F17028_DAISY-MINI-SHD



OPTICAL RESULTS (SIMULATED):



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)