

		A		B		C		D		E		F		G																																																																																
1	性能参数																																																																																													
	1. Heating current: Ui: AC250V, Ith: 3A 发热电流: Ui: AC250V, Ith: 3A					13. Compression torque: ≤ 3N 按压扭力: ≤3N																																																																																								
	2. Rated current:2A/DC36V 额定电流:2A/DC36V					14. Electrical life: 500000 cycles 电气寿命: 500000 cycles																																																																																								
	3. Insulation resistance:≥1000MΩ 绝缘电阻 :≥1000MΩ					15. mechanical: 500000cycles 机械寿命: 500000cycles																																																																																								
	4. Contact resistance:≤50mΩ 接触电阻 :≤50mΩ					16. Operation method:Self-locking 操作方式: 自锁式																																																																																								
	5. Pressing stroke:2.30mm ± 0.10 按压行程:2.30mm ± 0.10					17. NO reverse thrust foot torque: ≤30N NO反推脚扭力: ≤30N																																																																																								
	6. Contact stroke:1.00mm±0.10 接触行程 :1.00mm±0.10																																																																																													
	7. welding temperature: 320 ℃± 20 ℃ 焊接温度: 320 ℃± 20 ℃																																																																																													
	8. Welding duration: Less than 3 seconds in duration 焊接时长: Less than 3 seconds in duration																																																																																													
	9. Nut assembly torque:5-14N 螺帽装配力矩:5-14N																																																																																													
2	10. Protection level:IP65 防护等级:IP65																																																																																													
	11. Explosion prevention level: IK08 防暴等级: IK08																																																																																													
	12. Working environment temperature: -20 ℃~+55 ℃ 工作环境温度: -20 ℃~+55 ℃																																																																																													
3																																																																																														
4																																																																																														
5																																																																																														
<table><tr><td>A4</td><td></td><td></td><td></td><td rowspan="5"></td><td colspan="2" rowspan="2">COMMON TOLERANCE</td><td>UNIT</td><td>MM</td><td>PROJECTED</td><td></td><td colspan="4">PRODUCT NAME:</td></tr><tr><td>A3</td><td></td><td></td><td></td><td>DRAWN BY</td><td>FUYUAN</td><td>CHECKED BY</td><td>COCO</td><td colspan="4">MODEL NO: TP91211P1AB</td></tr><tr><td>A2</td><td></td><td></td><td></td><td>X.XX</td><td>± 0.10</td><td>DATE</td><td>2019</td><td>APPROVAL B</td><td>ALEN</td><td colspan="4">Https: www.rocpu.tw</td></tr><tr><td>A1</td><td></td><td></td><td></td><td>X.X</td><td>± 0.15</td><td colspan="9" rowspan="2">ROC PU TECHNOLOGY CO.,LTD</td></tr><tr><td>REV</td><td>DATE</td><td>REVISION</td><td>DESCRIPTION</td><td>ISSUE</td><td>X</td><td>± 0.25</td></tr><tr><td colspan="5"></td><td>ANGULAR</td><td>——</td><td colspan="9">Copies are issued in strict confidence and shall not be reproduced or copied,or used as the basic of manufacture or sale of apparatus without permission</td></tr></table>																A4					COMMON TOLERANCE		UNIT	MM	PROJECTED		PRODUCT NAME:				A3				DRAWN BY	FUYUAN	CHECKED BY	COCO	MODEL NO: TP91211P1AB				A2				X.XX	± 0.10	DATE	2019	APPROVAL B	ALEN	Https: www.rocpu.tw				A1				X.X	± 0.15	ROC PU TECHNOLOGY CO.,LTD									REV	DATE	REVISION	DESCRIPTION	ISSUE	X	± 0.25						ANGULAR	——	Copies are issued in strict confidence and shall not be reproduced or copied,or used as the basic of manufacture or sale of apparatus without permission								
A4					COMMON TOLERANCE		UNIT	MM	PROJECTED		PRODUCT NAME:																																																																																			
A3							DRAWN BY	FUYUAN	CHECKED BY	COCO	MODEL NO: TP91211P1AB																																																																																			
A2					X.XX	± 0.10	DATE	2019	APPROVAL B	ALEN	Https: www.rocpu.tw																																																																																			
A1					X.X	± 0.15	ROC PU TECHNOLOGY CO.,LTD																																																																																							
REV	DATE	REVISION	DESCRIPTION		ISSUE	X										± 0.25																																																																														
					ANGULAR	——	Copies are issued in strict confidence and shall not be reproduced or copied,or used as the basic of manufacture or sale of apparatus without permission																																																																																							
		A		B		C		D		E		F		G																																																																																

	A	B	C	D	E	F	G	
1	材质参数							1
	10							
	9							
2	8	Base 底座	PA66	1	Black 黑色		2	
	7	Pin 引脚	Brass 黄铜	1	gold-plating 镀金			
	6	Contact material 接触材质	Silvering 镀银	1				
3	5	Base 基座	PA66	1	Black 黑色		3	
	4	Arm nut 固定螺帽	Brass 黄铜	1	nickeling 镀镍			
	3	Oring O型圈	Silica gel 硅胶	1				
4	2	Housing 外壳	Aluminum alloy 铝合金	1	Oxidized/Black 氧化/黑色		4	
	1	Key 按键	Aluminum alloy 铝合金	1	Oxidized/Black 氧化/黑色			
	NO 序号	Part name 部件名	Material 材料	QTY 数量	Remark 备注			
5	A4						5	
	A3							
	A2							
	A1							
	REV	DATE	REVISION	DESCRIPTION	ISSUE			
	A	B	C	D	E	F	G	
			COMMON TOLERANCE		UNIT	MM	PROJECTED	
			X.XX ± 0.10		DRAWN BY	FUYUAN	CHECKED BY	
			X.X ± 0.15		DATE	2019	APPROVAL B	
			X ± 0.25		PRODUCT NAME:			
			ANGULAR		MODEL NO: TP91211P1AB			
					Https: www.rocpcu.tw			
					ROCPCU TECHNOLOGY CO.,LTD			
					Copies are issued in strict confidence and shall not be reproduced or copied,or used as the basic of manufacture or sale of apparatus without permission			