




A4					 台普 ROCPCU	COMMON TOLERANCE		UNIT	MM	PROJECTED		PRODUCT NAME:
A3								DRAWN BY	FUYUAN	CHECKED BY	COCO	MODEL NO: TP91214P124RA
A2								DATE	2019	APPROVAL B	ALEN	Https: www.rocpcu.tw
A1								ROCPCU TECHNOLOGY CO.,LTD				
REV	DATE	REVISION	DESCRIPTION	ISSUE		ANGULAR		Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission				

A		B		C		D		E		F		G	
1	性能参数												
	1. Heating current: Ui: AC250V, Ith: 3A 发热电流: Ui: AC250V, Ith: 3A												
	2. Rated current:2A/DC36V 额定电流:2A/DC36V												
	3. Insulation resistance:≥1000MΩ 绝缘电阻 :≥1000MΩ												
	4. Contact resistance:≤50mΩ 接触电阻 :≤50mΩ												
	5. Pressing stroke:2.30mm ± 0.10 按压行程:2.30mm ± 0.10												
	6. Contact stroke:1.00mm±0.10 接触行程 :1.00mm±0.10												
	7. welding temperature: 320 ℃± 20 ℃ 焊接温度: 320 ℃± 20 ℃												
	8. Welding duration: Less than 3 seconds in duration 焊接时长: Less than 3 seconds in duration												
	9. Nut assembly torque:5-14N 螺帽装配力矩:5-14N												
2	10. Protection level:IP65 防护等级:IP65												
	11. Explosion prevention level: IK08 防暴等级: IK08												
	12. Working environment temperature: -20 ℃~+55 ℃ 工作环境温度: -20 ℃~+55 ℃												
	13. Compression torque: ≤ 3N 按压扭力: ≤3N												
	14. Electrical life: 500000 cycles 电气寿命: 500000 cycles												
	15. mechanical: 500000cycles 机械寿命: 500000cycles												
	16. Operation method:Self-locking 操作方式: 自锁式												
	17. NO reverse thrust foot torque: ≤30N NO反推脚扭力: ≤30N												
	18. LED lamp power consumption: 20m以下 LED灯功耗: 20m以下												
	19. LED lamp lifespan: 40000h LED寿命: 40000h												
3	20. LED color: Red LED颜色: 红色												
4													
5													

A4				 台普 ROCPCU	COMMON TOLERANCE		UNIT	MM	PROJECTED		PRODUCT NAME:		
A3							DRAWN BY	FUYUAN	CHECKED BY	COCO	MODEL NO: TP91214P124RA		
A2						DATE	2019	APPROVAL B	ALEN	Https: www.rocpcu.tw			
A1					ROCPCU TECHNOLOGY CO.,LTD								
REV	DATE	REVISION	DESCRIPTION		ISSUE	ANGULAR		Copies are issued in strict confidence and shall not be reproduced or copied,or used as the basic of manufacture or sale of apparatus without permission					
A		B		C		D		E		F		G	

A		B		C		D		E		F		G	
材质参数													
1	10	luminous zone 发光区		PC 塑料		1							
	9	LEDpin LED脚		Brass 黄铜		1		Silvering 镀银					
2	8	Base 底座		PA66		1		Black 黑色					
	7	Pin 引脚		Brass 黄铜		1		gold-plating 镀金					
3	6	Contact material 接触材质		Silvering 镀银		1							
	5	Base 基座		PA66		1		Black 黑色					
4	4	Arm nut 固定螺帽		Brass 黄铜		1		nickeling 镀镍					
	3	Oring O型圈		Silica gel 硅胶		1							
5	2	Housing 外壳		Aluminum alloy 铝合金		1		Oxidized/Black 氧化/黑色					
	1	Key 按键		Aluminum alloy 铝合金		1		Oxidized/Black 氧化/黑色					
NO 序号		Part name 部件名		Material 材料		QTY 数量		Remark 备注					

A4				 台普 ROCPCU	COMMON TOLERANCE		UNIT	MM	PROJECTED		PRODUCT NAME:		
A3							DRAWN BY	FUYUAN	CHECKED BY	COCO	MODEL NO: TP91214P124RA		
A2					X.XX ± 0.10		DATE	2019	APPROVAL B	ALEN	Https: www.rocpcu.tw		
A1					X.X ± 0.15		ROCPCU TECHNOLOGY CO.,LTD						
					X ± 0.25								
REV	DATE	REVISION	DESCRIPTION		ISSUE	ANGULAR		Copies are issued in strict confidence and shall not be reproduced or copied,or used as the basic of manufacture or sale of apparatus without permission					
A		B		C		D		E		F		G	