
COAXIAL SURGE PROTECTOR DEVICE, GDT technology up to 1.0 GHz 3401.17.K

Properties

- · Broadband frequency operation from DC to 1 GHz
- · Gas discharge tube replaceable and not included
- · DC/AC remote powering via coaxial same cable
- · Surge current handling capability 30 kA once and 20 kA multiple
- · Semper self-extinguishing functionality optional









Product configuration		
Main path connectors	Port 1: unprotected, N jack (female)	
	Port 2: protected, N jack (female)	
Mounting and grounding	MH12 (bulkhead mounting)	
Side of bulkhead	protected side	
Capsule holder with chain	YES	
EMP can be install reversed	YES	

Interface and material data		
Housing material / plating	Brass / SUCOPLATE (R) Plating	
Center contact, material / plating	Port 1: Copper Beryllium Alloy / Gold Plating (without Nickel underplating)	
	Port 2: Copper Beryllium Alloy / Gold Plating (without Nickel underplating)	

Electrical data		
Impedance	50 Ω	
Frequency frame	0 MHz to 1000 MHz	
Return loss typical	≥ 26.44 dB	
Insertion loss typical	≤ 0.1 dB	
CW power frame	≤ 150 W	
Residual pulse energy (typ.)	350 μJ (test pulse 4 kV 1.2/50 μs; 2 kA 8/20 μs)	
Residual pulse voltage (typ.)	650 V (test pulse 4 kV 1.2/50 μs; 2 kA 8/20 μs)	
Surge current handling capability	30 kA single, 20 kA multiple (test pulse 8/20 μs)	



COAXIAL SURGE PROTECTOR DEVICE, GDT technology up to 1.0 GHz

3401.17.K

Electrical remarks	
Gas tube	Yes DC, GDT not included
Electrical remarks	Data refer to GDT 9071.99.0547, 230 V
Mechanical data	
Weight	110 g
Mating cycles	500
Environmental data	
Operation temperature	-40 °C 85 °C
Storage temperature	-40 °C 85 °C
Ingress protection (IP Rating)	IP66
Thermal shock according	MIL-STD-202, Method 107, Cond. B
Vibration according	MIL-STD-202, Method 204, Cond. D
Moisture resistance according	MIL-STD-202, Method 106
Comment	
NATO Stock Number	5920-12-321-2510
Ordering Information Table	
Item number	Item description
22643812	3401.17.K

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.

DOCUMENT PIM-P2027 / Date of publication: 31.10.2024 / uncontrolled copy

