

OP05CA Series open LED protectors provide a switching electronic shunt path when an LED in an LED string fails as an open circuit. This ensures that the remaining string of LEDs will continue to function if a single LED does not. OP05CA Series devices were designed to enable higher reliability in indoor LED lighting applications such as advertisement lighting and other applications. Additionally, they are molded from white material to make them


less visible in the LED fixture and the white molding also reflects more light to improve overall light engine efficiency. Compatible with one, two and three watt LEDs that have a nominal 3V forward characteristic, OP05CA Series devices are available in SMA surface mount package. The DO-214AC (SMA) low profile package is ideal for dense board applications.



## 产品特点 Product Features

- Fast switching
- Automatically resets after power cycle
- Low profile, small foot print standard DO-214AC package
- Compatible with industrial lighting environments
- Compatible with PWM frequencies up to 30 kHz
- RoHS compliant and halogen-free


## 原理图符号 Schematic Symbol



## 电子特性 Electrical Characteristics

Part	Symbol	Parameter	Conditions	MIN	TYP	MAX	Unit
OP05CA	V <sub>TO</sub>	Turn-On Voltage		5	10	12	V
	I <sub>S</sub>	Switching Current				20	mA
	I <sub>OS</sub>	On-State Current			1	1.5	A
	V <sub>OS</sub>	On-State Voltage	I <sub>AK</sub> = 1A		1	1.3	V
	I <sub>DRM</sub>	Leakage Current	V <sub>AK</sub> = 3.5 V		10	15	μA
	V <sub>ESD</sub>	ESD Withstand Voltage1	IEC61000-4-2 (Contact)	± 8			kV
			IEC61000-4-2 (Air)	± 15			kV

## Thermal Considerations

Package	Symbol	Parameter	Value	
DO-214AC 	$T_J$	Operating Junction Temperature Range	-40 to +150°C	
	$T_S$	Storage Temperature Range	-65 to +150°C	
	$R_{\theta JA}$	Thermal Resistance: Junction to Ambient	DO-214AA: 90 <sup>1</sup> DO-214AA: 90 <sup>2</sup>	

### Notes:

1) Standard FR-4 PCB with Copper Pads (Recommended Size)

2) Aluminum PCB

Thickness: 1.6mm


Grade: 1-2 W/mK Thermal Conductivity

Trace thickness: 2 oz

Insulation layer thickness: 215 um

Solder Pad Dimensions: 2.0mm x 2.8mm (Recommended Size)

## 尺寸图 DIMENSIONS



Unit:mm

DIM	Inches		Millimeters	
	Min	Max	Min	Max
A	0.049	0.065	1.250	1.650
B	0.157	0.177	3.990	4.500
C	0.100	0.110	2.540	2.790
D	0.078	0.090	1.980	2.290
E	0.030	0.060	0.780	1.520
F	-	0.008	-	0.203
G	0.194	0.208	4.930	5.280
H	0.006	0.012	0.152	0.305
I	0.070	-	1.800	-
J	0.082	-	2.100	-
K	-	0.090	-	2.300
L	0.082	-	2.100	-

## RuiLongYuan Electronics Co., Ltd.

---

- Reproducing and modifying information of the document is prohibited without permission from Ruilongyuan International Inc.
- Ruilongyuan International Inc. reserves the rights to make changes of the content herein the document anytime without notification. Please refer to our website for the latest document.
- Ruilongyuan International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Ruilongyuan International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Ruilongyuan International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Ruilongyuan International Inc. for any damages resulting from such improper use or sale.

---

**Tel: +86-755-8290 8296**

**Fax: +86-755-8290 8002**

**E-mail: jack@ruilon.com**