





- ▼ Capable of 2.5V Gate Drive
- ▼ Lower Gate Charge
- ▼ Fast Switching Performance
- ▼ RoHS Compliant & Halogen-Free



$BV_{DSS}$	20V
$R_{DS(ON)}$	75mΩ
$I_D$	3.5A



## Description

AP2N075E series are from Advanced Power innovated design and silicon process technology to achieve the lowest possible on-resistance and fast switching performance. It provides the designer with an extreme efficient device for use in a wide range of power applications.

The SOT-23S package is widely preferred for commercial-industrial surface mount applications and suited for low voltage applications such as DC/DC converters.

## Absolute Maximum Ratings@ $T_j=25^\circ\text{C}$ (unless otherwise specified)

Symbol	Parameter	Rating	Units
$V_{DS}$	Drain-Source Voltage	20	V
$V_{GS}$	Gate-Source Voltage	$\pm 12$	V
$I_D @ T_A = 25^\circ\text{C}$	Drain Current <sup>3</sup> , $V_{GS} @ 4.5\text{V}$	3.5	A
$I_D @ T_A = 70^\circ\text{C}$	Drain Current <sup>3</sup> , $V_{GS} @ 4.5\text{V}$	2.8	A
$I_{DM}$	Pulsed Drain Current <sup>1</sup>	10	A
$P_D @ T_A = 25^\circ\text{C}$	Total Power Dissipation	1.25	W
$T_{STG}$	Storage Temperature Range	-55 to 150	°C
$T_J$	Operating Junction Temperature Range	-55 to 150	°C

## Thermal Data

Symbol	Parameter	Value	Unit
$R_{thj-a}$	Maximum Thermal Resistance, Junction-ambient <sup>3</sup>	100	°C/W



## Electrical Characteristics@ $T_j=25^\circ\text{C}$ (unless otherwise specified)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
$\text{BV}_{\text{DSS}}$	Drain-Source Breakdown Voltage	$\text{V}_{\text{GS}}=0\text{V}, \text{I}_D=250\mu\text{A}$	20	-	-	V
$\text{R}_{\text{DS(ON)}}$	Static Drain-Source On-Resistance <sup>2</sup>	$\text{V}_{\text{GS}}=4.5\text{V}, \text{I}_D=3.5\text{A}$	-	-	75	$\text{m}\Omega$
		$\text{V}_{\text{GS}}=2.5\text{V}, \text{I}_D=1.2\text{A}$	-	-	125	$\text{m}\Omega$
$\text{V}_{\text{GS(th)}}$	Gate Threshold Voltage	$\text{V}_{\text{DS}}=\text{V}_{\text{GS}}, \text{I}_D=250\mu\text{A}$	0.5	-	1.2	V
$\text{g}_{\text{fs}}$	Forward Transconductance	$\text{V}_{\text{DS}}=10\text{V}, \text{I}_D=3\text{A}$	-	16	-	S
$\text{I}_{\text{DSS}}$	Drain-Source Leakage Current	$\text{V}_{\text{DS}}=16\text{V}, \text{V}_{\text{GS}}=0\text{V}$	-	-	10	$\mu\text{A}$
$\text{I}_{\text{GSS}}$	Gate-Source Leakage	$\text{V}_{\text{GS}}= \pm 12\text{V}, \text{V}_{\text{DS}}=0\text{V}$	-	-	+30	$\mu\text{A}$
$\text{Q}_{\text{g}}$	Total Gate Charge	$\text{I}_D=3\text{A}$	-	6.5	10.4	nC
$\text{Q}_{\text{gs}}$	Gate-Source Charge	$\text{V}_{\text{DS}}=10\text{V}$	-	1	-	nC
$\text{Q}_{\text{gd}}$	Gate-Drain ("Miller") Charge	$\text{V}_{\text{GS}}=4.5\text{V}$	-	1.6	-	nC
$t_{\text{d(on)}}$	Turn-on Delay Time	$\text{V}_{\text{DS}}=10\text{V}$	-	6	-	ns
$t_{\text{r}}$	Rise Time	$\text{I}_D=1\text{A}$	-	11	-	ns
$t_{\text{d(off)}}$	Turn-off Delay Time	$\text{R}_G=3.3\Omega$	-	14	-	ns
$t_{\text{f}}$	Fall Time	$\text{V}_{\text{GS}}=5\text{V}$	-	2.5	-	ns
$\text{C}_{\text{iss}}$	Input Capacitance	$\text{V}_{\text{GS}}=0\text{V}$	-	520	832	pF
$\text{C}_{\text{oss}}$	Output Capacitance	$\text{V}_{\text{DS}}=10\text{V}$	-	65	-	pF
$\text{C}_{\text{rss}}$	Reverse Transfer Capacitance	f=1.0MHz	-	60	-	pF

## Source-Drain Diode

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
$\text{V}_{\text{SD}}$	Forward On Voltage <sup>2</sup>	$\text{I}_S=1\text{A}, \text{V}_{\text{GS}}=0\text{V}$	-	-	1.2	V
$t_{\text{rr}}$	Reverse Recovery Time	$\text{I}_S=3\text{A}, \text{V}_{\text{GS}}=0\text{V},$ $d\text{I}/dt=100\text{A}/\mu\text{s}$	-	6	-	ns
			-	1.5	-	nC

## Notes:

- 1.Pulse width limited by Max. junction temperature.
- 2.Pulse test
- 3.Surface mounted on 1 in<sup>2</sup> copper pad of FR4 board, t ≤ 10s ; 300°C/W when mounted on min. copper pad.

THIS PRODUCT IS SENSITIVE TO ELECTROSTATIC DISCHARGE, PLEASE HANDLE WITH CAUTION.

USE OF THIS PRODUCT AS A CRITICAL COMPONENT IN LIFE SUPPORT OR OTHER SIMILAR SYSTEMS IS NOT AUTHORIZED.

APEC DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

APEC RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN.




Fig 1. Typical Output Characteristics




Fig 2. Typical Output Characteristics




Fig 3. On-Resistance v.s. Gate Voltage




Fig 4. Normalized On-Resistance v.s. Junction Temperature




Fig 5. Forward Characteristic of Reverse Diode







Fig 6. Gate Threshold Voltage v.s. Junction Temperature




**Fig 7. Gate Charge Characteristics**




**Fig 8. Typical Capacitance Characteristics**




**Fig 9. Maximum Safe Operating Area**




**Fig 10. Effective Transient Thermal Impedance**




**Fig 11. Transfer Characteristics**



**Fig 12. Gate Charge Circuit**



**Fig 13. Total Power Dissipation**




**Fig 14. Typ. Drain-Source on State Resistance**



**AP2N075EN**

---

## **MARKING INFORMATION**



Part Number : A21

Date Code : SS

SS:2004,2008,2012,2016,2020...

SS:2003,2007,2011,2015,2019...


SS:2002,2006,2010,2014,2018...

SS:2001,2005,2009,2013,2017...




ADVANCED POWER ELECTRONICS CORP.

## Package Outline : SOT-23S



SYMBOLS	Millimeters		
	MIN	NOM	MAX
A	0.80	1.00	1.20
A1	0.00	—	0.10
A2	0.05	—	0.20
D1	0.30	0.40	0.50
e	1.80	1.90	2.00
D	2.80	2.90	3.10
E	2.10	2.40	2.70
E1	1.20	1.30	1.40
M	0°	5°	10°
L	0.20	—	0.60



1. All Dimension Are In Millimeters.

2. Dimension Does Not Include Mold Protrusions.

Draw No. M1-N3MIBF-G-v04



---

**SOT-23S FOOTPRINT :**

