

REV.	DESCRIPTION	DATE
A/0	新版发行	2018.11.28

General tolerances(mm)														0.1/10
0 ~ 3	>3 ~ 6	>6 ~ 10	>10 ~ 18	>18 ~ 30	>30 ~ 50	>50 ~ 80	>80 ~ 120	>120 ~ 180	>180 ~ 250	>250 ~ 315	>315 ~ 400	>400 ~ 500	>500	
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	±2°

Product model	PIN	A	B
BX-DGRK-5.08-2P	2	11.66	5.08
BX-DGRK-5.08-3P	3	16.74	10.16
BX-DGRK-5.08-4P	4	21.82	15.24
BX-DGRK-5.08-5P	5	26.90	20.32
BX-DGRK-5.08-6P	6	31.98	25.40
BX-DGRK-5.08-7P	7	37.06	30.48
.....			
BX-DGRK-5.08-24P	24	5.08xN+1.5	5.08X(N-1)

UL Standard	B	C	D
Rated Voltage(V)/Current(A)	300/15	/	300/10
IEC Standard			
Overvoltage Category/Pollution Degree	Ⅲ/3	Ⅱ/2	Ⅱ/2
Rated Voltage(V)/Current(A)	/	320/20	/
Withstanding voltage(V/1Min)	AC2000		
Torque Tightening(N·m/Lb.in)	M2.5, 0.4/3.54		
Wire Range(rigid and flexible)(mm²/AWG)	0.2~2.5/28~12		
Pitch(mm)/Poles	5.08/N=02~24P		
Stripping length(mm)	7~8		
Operating temperature(°C)	-40~+105		
Conform to RoHS	Yes		

5	Screws	Steel	M2.5/Zn Plated
4	Cage	Copper alloy	Ni plated
3	Pin	Copper	Sn plated
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

2	端子 Contact	黄铜	n×1	电镀铜: 整个表面镀层≥30u"MIN, 厚度≥ 80u"MIN.
1	基座 Wafer	PA66(UL94V-0)	1	白色
序号	名称	材料	数量	备注

GENERAL TOLERANCES				DRAWN BY	Bossie (博锡)		
0.X	±0.25	X.°	±3°	CHK.BY			
0.XX	±0.12			APRV.BY			
0.XXX	±0.05	X.X°	±0.5°			SHEET	PROD. NAME Socket-type terminal
UNIT	SIZE	SCALE		DRAWING NO.	1 OF 1	PART NO.	BX-DGRK-5.08-NP
MM	A4	1:1			TITLE		

