

Product Description

Winchester's Bomar brand 300 Series 50 Ohm BNC Cable Plug Connectors can be used in a wide range of applications including Broadcast, Telecommunications, Test and Measurement, Security, and Medical.

The 300 Series 50 Ohm BNC Cable Plug Connectors are quick-connect/ quick-disconnect connectors that are easy to mate and un-mate with only a quarter turn of the coupling nut.

Designed to accommodate a large variety of RG cables and industry standard cables, Winchester's Bomar brand 300 Series 50 Ohm BNC Cable Plug Connectors feature a crimp/crimp termination.

A full line of printed circuit board receptacles, bulkhead receptacles, resistor terminations, and other accessories are also available.



 Bayonet coupling system ensures positive locking and allows quick and easy mating and un-mating of connectors.



 BNC cable plugs feature a captivated center contact. The retention barb prevents the contact from backing out the rear of the connector while a "nail head" feature at the crimp end prevents the contact from being over inserted into the connector.



 Coupling Nuts are stamped with Bomar name and part number for easy identification in the field.



Specifications

Electrical Impedance:

50 Ohms

Frequency Range: 0 – 4 GHz Working Voltage: 500 VRMS

Dielectric

500 VRMS at Sea Level

Withstanding Voltage:

1500 VRMS at Sea Level

VSWR:

Straight: 1.5 Max

Contact Resistance:

Center Contact: ≤ 3 Milliohms

Insulation Resistance:

5000 Megohms Min

Insertion Loss:

0.2dB Max

Environmental

Temperature Range: - 40° C to +165° C

Material

Body and Outer Contacts: Brass, Nickel Plated Male Contact: Brass, Gold Plated

Insulator: PTFE

Crimp Ferrule: Copper or Brass,

Nickel Plated

Mechanical

Coupling Nut Retention: 101 lbs. Center Contact Retention: \geq 6 lbs. Engagement Force: \leq 5 lbs. Disengagement Force: \geq 1.5 lbs.

Durability (Mating): 500 Cycles Min.



Part Numbers

Bomar Part Number	Straight Cable Plugs	Crimp Tool with Die	Hex Size	Packaging
310A205MV	RG174, RG316, LMR100	BDHD200	.068 / .213	Single
310A205M	RD316	BDHD200	.068 / .213	Single
310A205F	RG58, RG141, RG142, LMR195 Stranded	BDHD200	.068 / .213	Single
310A205FS	RG 58, LMR 195 Solid Center Conductor	BDHD200	.068 / .213	Single
310A205A	RG6, 21 AWG Center Conductor	BDHD200	Solder / .288	Single
310A205A18	RG6 CATV 18 AWG Center conductor	BDHD200	.068 / .288	Single

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Winchester Interconnect: 310A205S