





OPERATING CHARACTERISTICS AT 25° C AMBIENT										
DIALIGHT PART NUMBER	LED COLOR	LED CHIP	IF (mA)	FORWARD VOLTAGE (V)		LUMINOUS INTENSITY (mcd)		REVERSE CURRENT mA @VR=4V	PEAK WAVELENGTH (nm)	VIEWING ANGLE (DEGREES)
				TYP	MAX	MIN	TYP	MAX		
597-3301-502SF,507SF	GREEN	GaP	20	2.2	2.8	5.6	25.0	100	570	104
597-3401-502SF,507SF	YELLOW	GaAsP	20	2.1	2.8	2.2	6.3	100	585	104
597-3602-502SF,507SF	BLUE	InGaN	20	3.3	4.3	36	100	100	468	110




ATTENTION:
OBSERVE PRECAUTIONS FOR
HANDLING ELECTROSTATIC
SENSITIVE DEVICES

REV	REVISIONS	DRN	CKD	DATE
A	NEW RELEASE	LD	NO	10-15-19
B	REVISED NOTE 1, WAS EPOXY COLOR : WATER CLEAR	LD	NO	10-22-19



TAPE AND REEL SPECIFICATION




RECOMMENDED SOLDER PAD LAYOUT


Mark	Meanings	Conditions
Ts _{max}	Maximum of pre-heating temperature	180°C
Ts _{min}	Minimum of pre-heating temperature	140°C
Ts	Time from Ts _{min} to Ts _{max}	Over 60sec.
T _L	Reference temperature	210~250°C
t _L	Retention time for T _L	Within 40sec.
T _p	Peak temperature	250°C(Max)
t _p	Time for peak temperature	Within 10sec.
ΔT _R /Δt	Temperature rising rate	Under 3°C/sec.
ΔT _D /Δt	Temperature decreasing rate	Over -3°C/sec.

NOTES:

- SILICONE LENS COLOR IS NON TINTED DIFFUSED.
- LEADS: GOLD PLATED.
- SOLDER ADHERANCE: BOTH LEADS PER MIL. STD. 202E, METHODE 208C.
- LABELING: REELS TO BE IDENTIFIED WITH DIALIGHT P/N, QUANTITY, DATE CODE, AND INTENSITY BIN CATEGORY.
- PIN NUMBERS ARE FOR REFERENCE ONLY, DESIGNATION NON-EXISTENT ON PART.
- THIS ASSEMBLY CONTAINS ELECTROSTATIC DISCHARGE SENSITIVE DEVICES (ESDS). MAINTAIN ALL PRECAUTIONARY MEASURES DURING ASSEMBLY, HANDLING, AND STORAGE IN ACCORDANCE WITH IPC-A-610.
- THIS PRODUCT IS ROHS COMPLIANT. EACH BAG IS TO BE MARKED WITH ROHS COMPLIANT LABEL OR EQUIVALENT MARKINGS. LED MUST BE Pb FREE (ROHS COMPLIANT).
- MOISTURE SENSIVITY LEVEL 3

ABSOLUTE MAXIMUM RATINGS AT 25° C AMBIENT	GREEN, YELLOW	BLUE	UNITS
POWER DISSIPATION	70	84	mW
DERATE LINEARLY FROM 25° C	0.42	.40	mA/° C
CONTINUOUS FORWARD CURRENT	25	20	mA
PEAK FORWARD CURRENT (1ms PULSE WIDTH, 1/5 DUTY CYCLE)	60	100	mA
REVERSE VOLTAGE	4	5	V
OPERATING TEMPERATURE	-30 TO +85	-30 TO +85	°C
STORAGE TEMPERATURE	-40 TO +85	-40 TO +100	°C



THIS DRAWING AND THE CONTENTS HEREIN ARE CONFIDENTIAL AND THE SOLE PROPERTY OF DIALIGHT CORP. REPRODUCTION OF THIS DRAWING OR CONSTRUCTION OF ANY PARTS WITHIN THIS DRAWING ARE FORBIDDEN WITHOUT THE WRITTEN CONSENT OF DIALIGHT CORP.		
SCALE: 12.000 ALL DIM's: INCH (mm)	DRAWING NUMBER C-18451	REV B
TOLERANCES: UNLESS OTHERWISE SPECIFIED FRACTIONS: ± 1/64 DECIMALS (.XX): ± .02 DECIMALS (.XXX): ± .008 ANGLES: ± 1° FINISH -	TITLE 1208 PKG LED SILICONE LENS	
	MATERIAL -	
	 1501 ROUTE 34 SOUTH FARMINGDALE, NJ 07727 (732) 919-3119 www.dialight.com	
FSCM 83330	SHEET 1 OF 1	FAMILY TABLE:

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Dialight:

[597-3602-50-7SF](#) [597-3401-50-7SF](#) [597-3301-50-7SF](#)