

SMD High Current Molded Inductors - FCH0420 - Series

FCH0420-Series

●Features:


- Ultra low cost
- Shielded constructions
 - High frequency range up to 5MHz
- Very low DC resistance
- Low Noise
- RoHS compliant

●Applications:

- PDA/Notebook/Desktop/Server applications
- DC/DC converter




1.Shapes and Dimensions (形状及尺寸)




Type	A	B	C	D	E
FCH0420	4.6±0.3	4.1±0.3	2.0 MAX	1.1±0.3	2.0±0.3

2.Schematic:



3.layout recommendation:(mm)



SMD High Current Molded Inductors -FCH0420- Series

4.FCH0420-Series:

Part Number (品名)	Inductance (uH) ±20% (电感值)	DCR(mΩ) (直流阻抗)		Isat DC Current (饱和电流)	Irms DC Current (温升电流)
		Typical	MAX	(A) Typ	(A) Typ
FCH0420-R10Y	0.1±30%	3.8	4.2	15.0	14.0
FCH0420-R22M	0.22	4.0	6.3	13.0	8.0
FCH0420-R33M	0.33	9.0	11.0	12.0	10.0
FCH0420-R47M	0.47	10	12	10.0	6.5
FCH0420-R56M	0.56	11	14.0	9.0	6.5
FCH0420-R68M	0.68	17	20	8.0	5.0
FCH0420-1R0M	1.00	23	27	7.0	5.0
FCH0420-1R2M	1.20	24	29	6.5	5.0
FCH0420-1R5M	1.50	30	36	6.5	4.5
FCH0420-2R2M	2.20	41	49	5.0	4.0
FCH0420-3R3M	3.30	62	76	4.0	3.5
FCH0420-4R7M	4.70	101	127	3.5	3.0
FCH0420-5R6M	5.60	126	150	3.0	2.5
FCH0420-6R8M	6.80	137	157	2.5	2.2
FCH0420-8R2M	8.20	145	180	2.5	2.0
FCH0420-100M	10.00	181	243	2.0	1.8
FCH0420-150M	15.00	280	330	1.5	1.4
FCH0420-220M	22.00	401	500	1.3	1.2

Remark:

<1>Inductance: 100KHz 0.1V

<2>Tolerance of inductance:±20%

<3>Isat: The value of current indicates that inductance drops 30%(Typical) from its initial value

<4>Irms: The value of current indicates that the temperature of the coil is increase 40°C (Typical)

<5>Test condition: Ta= 25°C

Packaging Unit:3000PCS/R