1-965261-1 ACTIVE

AMP | Junior Power Timer, Timer Connector System

TE Internal #: 1-965261-1

Housing for Male Terminals, Wire-to-Panel, 4 Position, 5 mm [.197

in] Centerline, Sealable, Black, Wire & Cable, Power, Hybrid

View on TE.com >



Connectors > Automotive Connectors > Automotive Housings > Timer Connector Housing



Connector System: Wire-to-Panel

Number of Positions: 4

Connector & Housing Type: Housing for Male Terminals

Centerline (Pitch): 5 mm [.197 in]

Sealable: Yes

All Timer Connector Housing (511)

Features

Product Type Features

r roduct type roduction	
Mixed & Hybrid Connector	No
Connector Shape	Rectangular
Connector System	Wire-to-Panel
Connector & Housing Type	Housing for Male Terminals
Sealable	Yes
Connector & Contact Terminates To	Wire & Cable
Primary Locking Feature	On the Terminal
Configuration Features	
Number of Positions	4
Number of Rows	1
Electrical Characteristics	
Operating Voltage	14 VDC
Nominal Voltage Architecture	12 V
Body Features	
Cable Exit Angle	180°

Black

A1

Primary Product Color

Connector & Keying Code



Contact Features

Contact Size	2.8mm
Contact Type	Tab
Contact Current Rating (Max)	30 A

Mechanical Attachment

Terminal Position Assurance	No
Strain Relief	Without
Mating Alignment Type	Keyed
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)

Housing Features

Housing Material	PBT GF
Centerline (Pitch)	5 mm[.197 in]

Dimensions

Connector Height	20.6 mm[.811 in]
Product Width	39 mm[1.535 in]
Product Length	27.3 mm[1.075 in]

Usage Conditions

Operating Temperature (Max)	70 °C, 75 °C, 80 °C, 85 °C, 90 °C, 100 °C, 105 °C, 110 °C, 120 °C[158 °F][167 °F][176 °F][185 °F][194 °F][212 °F][221 °F][230 °F][248 °F]
Operating Temperature Range	-40 - 120 °C[-40 - 248 °F]

Operation/Application

Circuit Application	Power
Industry Standards	
UL Flammability Rating	UL 94HB

Packaging Features

Connector Position Assurance Capable

Packaging Method	Carton
Other	
Serviceable	No

No



Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts














TE Part # CAT-T4827-T273 TIMER, RECEPTACLE AND TAB



TE Part # 828904-1 SINGLE WIRE SEAL FOR J.P.T.CON



SEALING FOR 4POS. JPT HSG ASSY








Also in the Series | Junior Power Timer





Position Assurance(8)





Automotive Terminals(189)



Busbars & Terminals(1)



Connector Seals & Cavity Plugs(9)




Insertion & Extraction Tools(8)



Module Components(1)



Other Automotive Connector Accessories(2)



Also in the Series | Timer Connector System





Automotive Connector Caps & Covers (14)



Automotive Connector Locks & Position Assurance(15)



Automotive Housings(215)



Automotive Terminals(135)



Connector Seals & Cavity Plugs(36)



Crimp Terminal Housings(13)



Insertion & Extraction Tools(18)



Other Automotive Connector Accessories(1)



PCB Headers & Receptacles(40)



Quick Disconnects(4)

Customers Also Bought



TE Part #968393-1
Timer Connector Housing



TE Part #63522-1 250 FASTON TAB 20-15 AWG NPST



TE Part #2-962340-1 4P FLACHSTCK GEH2,8



TE Part #828904-1 SINGLE WIRE SEAL FOR J.P.T.CON

TE Part #5-1768384-3 LBF-LA0121

Documents

Housing for Male Terminals, Wire-to-Panel, 4 Position, 5 mm [.197 in] Centerline, Sealable, Black, Wire & Cable, Power, Hybrid



Product Drawings

FLACHSTE-GEH2,8 4P

English

CAD Files

Customer View Model

ENG_CVM_CVM_1-965261-1_B1.3d_stp.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-965261-1_B1.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1-965261-1_B1.3d_igs.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use