



8821WR-XXDP	Nylon UL94V-0	Brass	Tin Plated	8821H-D
Series No.	Material	Material	Metal plating	Mate with Housing

Specifications:

规格:

- Voltage rating: 250VAC/DC
额定电压: 250V AC/DC
- Current rating: 3A AC/DC
额定电流: 3A AC/DC
- Withstanding voltage: 1000V AC/minute
耐受电压: 1000V AC/分钟
- Temperature range: -25°C~+85°C
温度范围: -25°C~+85°C
- Insulation resistance: 1000MΩ MIN
绝缘电阻: 1000MΩ MIN
- Contact resistance: 10mΩ Max
接触电阻: 10mΩ Max

Circuits	Dimensions			
	A	B	C	D
2	2.50	7.50	6.00	3.00
3	5.00	10.00	8.50	3.00
4	7.50	12.50	11.00	3.80
5	10.00	15.00	13.50	6.30
6	12.50	17.50	16.00	8.80
7	15.00	20.00	18.50	11.30
8	17.50	22.50	21.00	13.85
9	20.00	25.00	23.50	16.40
10	22.50	27.50	26.00	18.90
11	25.00	30.00	28.50	21.40
12	27.50	32.50	31.00	23.90
13	30.00	35.00	33.50	26.50
14	32.50	37.50	36.00	29.00
15	35.00	40.00	38.50	31.50
16	37.50	42.50	41.00	34.00

ECN BO.		new		2015/5/3	A	瀚源
DESCRIPTION.		DATE.		REV.		
DESIGNED	CHECKED	APPROVAL	DRAWING NUMBER	SCALT: 1/2		SCALE: 3:1
Mikey	Tom	Jerry	PART NAME	8821WR-XXDP	UNLESS OTHERWISE SPECIFIED, TOLERANCE:	X. ±0.25
			MODEL NAME	H-8821WR-XXDP		X.x ±0.20
			3RD ANGLE PROJ	HanElectricity Co.,LTD		X.xx ±0.15
						ANGULAR ±3°
						FILE.NO.