

AMP | AMP MCP Connector System

TE Internal #: 1-1718484-1 Housing for Female Terminals, Wire-to-Wire, 25 Position, 4 mm / 5 mm [.157 in / .197 in] Centerline, Black, Wire & Cable, AMP MCP Connector System

View on TE.com >

Connectors > Automotive Connectors > Automotive Housings > AMP Unsealed Connector Housing



Connector System: Wire-to-Wire

Number of Positions: 25

Connector & Housing Type: Housing for Female Terminals

Centerline (Pitch): 4 mm, 5 mm [.157 in, .197 in]

Sealable: No

All AMP Unsealed Connector Housing (176)

ennectivity

Features

Product Type Features

Mixed & Hybrid Connector	Yes				
Connector Shape	Rectangular				
Connector System	Wire-to-Wire				
Connector & Housing Type	Housing for Female Terminals				
Sealable	No				
Connector & Contact Terminates To	Wire & Cable				
Primary Locking Feature	Integrated in Housing				
Configuration Features					
Number of Positions	25				
Number of Rows	3				
Electrical Characteristics					
Operating Voltage	36 VDC				

Housing for Female Terminals, Wire-to-Wire, 25 Position, 4 mm / 5 mm [.157 in / .197 in] Centerline, Black, Wire & Cable, AMP MCP Connector System



Body Features

Cable Exit Angle	180°					
Primary Product Color	Black					
Connector & Keying Code	A					
Contact Features						
Contact Size	1.5K, 2.8mm					
Contact Type	Receptacle					
Mating Tab Width	1.6 mm, 2.8 mm[.062 in][.11 in]					
Contact Current Rating (Max)	23 A, 29 A					
Mechanical Attachment						
Terminal Position Assurance	No					
Strain Relief	Without					
Mating Alignment Type	Keyed					
Mating Alignment	With					
Connector Mounting Type	Cable Mount (Free-Hanging)					
Housing Features						

Housing Material

PBT/ASA-GF20

4 mm, 5 mm[.157 in][.197 in]

Centerline (Pitch)

Dimensions

Connector Height	26 mm[1.02 in]				
Product Width	27.5 mm[1.08 in]				
Product Length	42.3 mm[1.66 in]				
Row-to-Row Spacing	4.2 mm, 8.1 mm[.165 in][.319 in]				
Usage Conditions					
Operating Temperature (Max)	120 °C[248 °F]				
Operating Temperature Range	-40 - 120 °C[-40 - 248 °F]				
Operation/Application					
Circuit Application	Power				
Industry Standards					
UL Flammability Rating	UL 94HB				
Packaging Features					
Packaging Quantity	900				

C For support call+1 800 522 6752

Housing for Female Terminals, Wire-to-Wire, 25 Position, 4 mm / 5 mm [.157 in / .197 in] Centerline, Black, Wire & Cable, AMP MCP Connector System



Packaging Method	Box
Other	
Serviceable	No
Connector Position Assurance Capable	No

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant			
EU ELV Directive 2000/53/EC	Compliant			
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold			
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC			
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free			
Solder Process Canability	Not applicable for solder process capability			

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Housing for Female Terminals, Wire-to-Wire, 25 Position, 4 mm / 5 mm [.157 in / .197 in] Centerline, Black, Wire & Cable, AMP MCP Connector System



TE Part # 1-1670614-2 36POS,MIXED,HEADER HSG,CONV. KIT 25POS

Also in the Series AMP MCP Connector System




Connector Seals & Cavity Plugs(5)	Insertion & Extraction Tools(13)	Other Automotive Connector	PCB Headers & Receptacles(28)
		Accessories(2)	

Customers Also Bought

TE Part #1-1718491-1 AMP Unsealed Connector Housing	TE Part #1-1718485-2 CARRIER FOR RECEPT. INSERTS 36 POS	TE Part #953122-3 40W MQS COVER ASSY (15D)	TE Part #953122-4 40W MQS COVER ASSY (15d)
	€ TE		
TE Part #2327104-4 CVTY PLUG,AMP 0.64,CVTY DIA,0.78, BLK	TE Part #CAR2SC68 CAR RECPT DIN9680 2way, IP68	TE Part #2361005-4 RING TONGUE TRMNL,50MMSQ	TE Part #2363494-1 GB/T AC,CHARGE INLET ASSY

Housing for Female Terminals, Wire-to-Wire, 25 Position, 4 mm / 5 mm [.157 in / .197 in] Centerline, Black, Wire & Cable, AMP MCP Connector System





Documents

Product Drawings CARRIER FOR RECEPTACLE INSERTS

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-1718484-1_D_c-1-1718484-1-d.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1-1718484-1_D_c-1-1718484-1-d.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-1718484-1_D_c-1-1718484-1-d.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Product Specifications Application Specification

German