

规格书 SPECIFICATION

客户 CUSTOMER	立创
客户料号 CUSTOMER P/N	
规格描述 DESCRIPTION	630V/1UF/K/卧式/L45/黄色扁形/28*22*12.5/ZNRC
产品编码 PART NUMBER	CFT2J105K0DR280NY100
日期 DATE	2024-05-22

德尔创承认栏 APPROVED BY DERSONIC			客户承认栏 APPROVED BY CUSTOMER	
批准 APPROVED BY	审核 CHECK BY	制订 FORMULATE BY	批准 APPROVED BY	审核 CHECK BY
				

东莞市德尔创电子有限公司

DONGGUAN DERSONIC ELECTRONIC CO., LTD.

中国广东省东莞市寮步镇松湖智谷科技产业园2栋15楼
15/F, Building 2, Songhu Zhigu Science and Technology Industrial Park,
Liaobu Town, Dongguan City, Guangdong Province, China
TEL: +86-769-8533 5208 FAX: +86-769-8155 5989
Website: <http://www.dersonic.com>

D	TECHNICAL PARAMETERS			PRODUCT DIMENSIONS					CUSTOMER P/N			
	ELECTRICAL CHARACTERISTICS :			Dimension(mm)								
				W (Max)	H (Max)	T (Max)	L (Min)	φd ±0.05				
	1	Rated capacitance(C _R)	1.0μF	CFT2J105K0DR280NY100								
	2	Capacitance tolerance	±10%									
	3	Rated voltage(VR)	630VDC									
	TEST PARAMETERS :											
	4	Voltage proof between terminals	Apply 1.5 times of U _R for 60 +/-5sec or 1.75 times of U _R for 2 sec.									
	5	Insulation resistance(IR* <i>C_R</i>)	CR≤0.33μF ≥30000MΩ CR>0.33μF ≥10000MΩ/uF (At 100VDC, 1min ,20~25 °C)									
	6	Dissipation factor(DF)	≦ 0.001(0.1%) at 1 KHz									
C	WORK ENVIRONMENT :											
	7	Climatic category	40/85/21									
	8	Operating temperature range	-40℃ to +85℃									
	9	Standard	IEC60384-16									
	CONSTRUCTION :											
B	10	Dielectric	Metallized polypropylene									
	11	Metal spray	Special Solder									
	12	Filler	Epoxy resin (UL 94V-0)									
	13	Outer envelope	Mylar Tape									
	14	Lead wire	Lead wire Diameter 0.8mm									
A	Other			Customer	Revise	Version	Signature	Date				
					Firstedition	1.0	丁愛弟	2023/07/11				
				Customer Signature	Check	Sales	QA	Cartography	Unit	Proportion	Model:	MPA
					莊育璋	史麗霞	何國勇	黃俊傑	mm	N.T.S	Drawing NO.	
			Page: 1/1					CC67923071108				