

100V N-Channel Power MOSFET

Description


D15NF10L-MNS, the uses advanced trench technology to provide excellent $R_{DS(ON)}$, low gate charge. It can be used in a wide variety of applications

KEY CHARACTERISTICS


- ① $V_{DS}=100V, I_D=15A$
 $R_{DS(ON)} < 90m\Omega @ V_{GS}=10V$
 $R_{DS(ON)} < 115m\Omega @ V_{GS}=4.5V$
- ② High density cell design for lower $R_{DS(on)}$
- ③ Fully characterized avalanche voltage and current
- ④ Good stability and uniformity with high E_{AS}
- ⑤ Excellent package for good heat dissipation

APPLICATIONS

- ① Power switching application
- ② Hard switched and High frequency circuits
- ③ Uninterruptible power supply



Schematic diagram



TO-252

ORDERING INFORMATION

Ordering Codes	Package	Product Code	Packing
D15NF10L-MNS	TO-252	D15NF10L	Reel

Absolute Maximum Ratings ($T_A=25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	Limit	Unit
Drain-Source Voltage	V_{DS}	100	V
Gate-Source Voltage	V_{GS}	± 20	V
Drain Current-Continuous	I_D	15	A
Drain Current-Pulsed (Note 1)	I_{DM}	45	A
Maximum Power Dissipation($T_c=25^\circ\text{C}$)	P_D	31	W
Single pulse avalanche energy(Note 2)	E_{AS}	21	mJ
Operating Junction and Storage Temperature Range	T_J, T_{STG}	-55 To 175	$^\circ\text{C}$

Thermal Characteristic

Thermal Resistance,Junction-to-Case	$R_{\theta JC}$	4.8	$^\circ\text{C/W}$
-------------------------------------	-----------------	-----	--------------------

Electrical Characteristics (T_A=25℃ unless otherwise noted)

Parameter	Symbol	Condition	Min	Typ	Max	Unit
Off Characteristics						
Drain-Source Breakdown Voltage	B _{VDSS}	V _{GS} =0V I _D =250μA	100	-	-	V
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} =100V,V _{GS} =0V	-	-	1	μA
Gate-Body Leakage Current	I _{GSS}	V _{GS} =±20V,V _{DS} =0V	-	-	±100	nA
On Characteristics						
Gate Threshold Voltage	V _{GS(th)}	V _{DS} =V _{GS} ,I _D =250μA	1	1.8	2.4	V
Drain-Source On-State Resistance(Note 3)	R _{DS(ON)}	V _{GS} =10V, I _D =5A	-	80	90	mΩ
		V _{GS} =4.5V, I _D =5A		90	115	
Forward Transconductance	g _{FS}	V _{DS} =25V,I _D =3.6A	-	5	-	S
Dynamic Characteristics						
Input Capacitance	C _{ISS}	V _{DS} =25V,V _{GS} =0V, f=1.0MHz	-	680	-	pF
Output Capacitance	C _{OSS}		-	110	-	pF
Reverse Transfer Capacitance	C _{rss}		-	85	-	pF
Switching Characteristics (Note 4)						
Turn-on Delay Time	t _{d(on)}	V _{DD} =50V,I _D =5A, V _{GS} =10V,R _{GEN} =2.5Ω	-	10	-	nS
Turn-on Rise Time	t _r		-	7	-	nS
Turn-Off Delay Time	t _{d(off)}		-	34	-	nS
Turn-Off Fall Time	t _f			9	-	nS
Total Gate Charge	Q _g	V _{DS} =80V,I _D =3A V _{GS} =10V	-	16	-	nC
Gate-Source Charge	Q _{gs}		-	4	-	nC
Gate-Drain Charge	Q _{gd}		-	5	-	nC
Drain-Source Diode Characteristics						
Diode Forward Voltage	V _{SD}	V _{GS} =0V,I _S =15A	-	-	1.2	V

Notes:

- 1.Repetitive Rating: Pulse width limited by maximum junction temperature.
- 2.E_{AS} condition :T_j=25℃, V_{DD}=50V, V_{GS}=10V, L=0.5mH, R_g=25Ω
- 3.Pulse Test: Pulse Width ≤ 300μs, Duty Cycle ≤ 2%.
- 4.Guaranteed by design, not subject to production.

Characteristics Curves

Figure 1 Output Characteristics




Figure 2 Transfer Characteristics




Figure 3 On-Resistance vs. I_D and V_{GS}




Figure 4 On-Resistance vs. Junction Temperature




Figure 5 On-Resistance vs. V_{GS}




Figure 6 Body Diode Forward Voltage




Figure 7 Gate-Charge Characteristics




Figure 8 Capacitance Characteristics




Figure 9 Maximum Forward Biased Safe Operation Area




Figure 10 Single Pulse Power Rating Junction-to-Ambient














Figure 11 Normalized Maximum Transient Thermal Impedance



Test Circuit and Waveform

Gate Charge Test Circuit 	Gate Charge Test Waveform 
Resistive Switching Test Circuit 	Resistive Switching Test Waveforms 
Unclamped Inductive Switching (UIS) Test Circuit 	Unclamped Inductive Switching (UIS) Test Waveforms 
Diode Recovery Test Circuit 	Diode Recovery Test Waveforms 

Package Description



Items	Values(mm)	
	MIN	MAX
A	6.30	6.90
A1	0	0.13
B	5.70	6.30
C	2.10	2.50
D	0.30	0.60
E1	0.60	0.90
E2	0.70	1.00
F	0.30	0.60
G	0.70	1.20
L1	9.60	10.50
L2	2.70	3.10
H	0.60	1.00
M	5.10	5.50
N	2.09	2.49
R	0.3	
T	1.40	1.60
Y	5.10	6.30

TO-252 Package

www.mns-kx.com



NOTE:

1. Exceeding the maximum ratings of the device in performance may cause damage to the device, even the permanent failure, which may affect the dependability of the machine. Please do not exceed the absolute maximum ratings of the device when circuit designing.
2. When installing the heat sink, please pay attention to the torsional moment and the smoothness of the heat sink.
3. MOSFETs is the device which is sensitive to the static electricity, it is necessary to protect the device from being damaged by the static electricity when using it.
4. Shenzhen Minos reserves the right to make changes in this specification sheet and is subject to change without prior notice.

CONTACT:

深圳市迈诺斯科技有限公司（总部）

地址：深圳市福田区华富街道田面社区深南中路4026号田面城市大厦22B-22C

邮编：518025

电话：0755-83273777