


REV.	ECN / DESCRIPTION	BY	DATE
A0	NEW	ZG.HU	2017.11.14





HOUSING: LCP,UL94V-0,BLACK.
 TERMINAL: PHOSPHOR BRONZE T=0.35MM,
 G/FU" GOLD PLATING ON CONTACT AREA.
 SHIELD: C2680,T=0.20MM,20 MIN NICKEL PLATING
 ON ALL AREA.

DURABILITY: 750 CYCLES MIN, 12.5MM/MINUTE.
 INSERTION FORCE: 2.2KG.F MAX.
 RETENTION STRENGTH : 7.7KG.F BETWEEN JACK AND PLUG.
 OPERATING TEMPERATURE: -40℃ ~ +85℃.
 STORAGE TEMPERATURE: -40℃ ~ +85℃.
 ALL CRITICAL DIMENSIONS WITH "※"

VOLTAGE: 125 VOLTS AC.
CURRENT RATING : 1.5AMP.
DIELECTRIC STRENGTH: 1000 VAC RMS 50HZ OR 60HZ,1MIN.
INSULATION RESISTANCE: 500 MEGA OHMS MIN. INITIAL
AFTER 500V DC FOR 1 MINUTE.
CONTACT RESISTANCE: SINGLE TERMINAL 30 MILLIOHMS MAX.
INITIAL 50 MILLIOHMS MAX. AFTER
DURABILITY TEST

LED Specification

Standard LED Color	LED Wavelength	Foward(A)	Foward(V)
Green	568nm	20mA	1.85-2.45V
Yellow	585nm	20mA	1.7-2.2V



东莞市美韩电子科技有限公司

Dongguan Usakro Electronic Technology Co., Ltd.

Tel : 0769-87869902

<http://www.usakro.com>

TITLE:
RJ45 沉板3.0 DIP带屏蔽带灯


PART NO.:	DGUKCB301188DB1W6DB1075
-----------	-------------------------

REMARK:

SIZE	UNITS
A4	MM[INCH]

SACLE
1:1

SHEET
1/1



GENERAL TOLERANCES
UNLESS SPECIFIED

	$x \pm 0.35$
--	--------------

$.x \pm 0.30$

	.xx±0.25
	xxx+0 10

APPROVED BY:
JP.Gong

CHECKED BY:

DESIGN BY:

ZG.Hu