

Product Summary

$V_{(BR)DSS}$	$R_{DS(on)TYP}$	I_D
100V	20mΩ@10V	35A
	25mΩ@4.5V	



合肥矽普半导体

Siliup Semiconductor Technology Co., Ltd

技术 品质 服务

www.siliup.com


Feature

- Fast Switching
- Low Gate Charge and Rdson
- Advanced Split Gate Trench Technology
- 100% Single Pulse avalanche energy Test

Applications


- Power switching application
- DC-DC Converter

Package




TO-252(1:G 2:D 3:S)

Circuit diagram



Marking



Order Information

Device	Package	Unite/Tape
SP010N20GTH	TO-252	2500

Absolute maximum ratings (Ta=25°C unless otherwise noted)

Parameter	Symbol	Rating	Units
Drain-Source Voltage	V_{DS}	100	V
Gate-Source Voltage	V_{GS}	± 20	V
Continuous Drain Current (Tc=25°C)	I_D	35	A
Pulsed Drain Current ²	I_{DM}	140	A
Single Pulse Avalanche Energy ³	E_{AS}	79	mJ
Total Power Dissipation ⁴ (Tc=25°C)	P_D	105	W
Thermal Resistance Junction-Case ¹	$R_{\theta JC}$	1.19	°C/W
Storage Temperature Range	T_{STG}	-55 to 150	°C
Operating Junction Temperature Range	T_J	-55 to 150	°C

Electrical characteristics (Ta=25°C, unless otherwise noted)


Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Static Characteristics						
Drain-Source Breakdown Voltage	BV _{DSS}	VGS=0V , ID=250uA	100	---	---	V
Drain-Source Leakage Current	IDSS	VDS=80V , VGS=0V , TJ=25℃	---	---	1	uA
Gate-Source Leakage Current	IGSS	VGS=±20V , VDS=0V	---	---	±100	nA
Gate Threshold Voltage	VGS(th)	VGS=VDS , ID =250uA	1.0	1.8	2.5	V
Static Drain-Source On-Resistance ²	RDS(ON)	VGS=10V , ID=20A	---	20	25	mΩ
		VGS=4.5V , ID=20A	---	25	33	
Dynamic Characteristics						
Input Capacitance	Ciss	VDS=50V , VGS=0V , f=1MHz	---	695	---	pF
Output Capacitance	Coss		---	151	---	
Reverse Transfer Capacitance	Crss		---	9	---	
Switching Characteristics						
Total Gate Charge	Qg	VDS=50V , VGS=10V , ID=20A	---	14.6	---	nC
Gate-Source Charge	Qgs		---	2.3	---	
Gate-Drain Charge	Qgd		---	4.2	---	
Turn-On Delay Time	Td(on)	VDD=50V , VGS=10V , RG=3Ω , ID=20A	---	6.6	---	ns
Rise Time	Tr		---	2	---	
Turn-Off Delay Time	Td(off)		---	19	---	
Fall Time	Tf		---	2.3	---	
Source-Drain Diode Characteristics						
Diode Forward Voltage ²	VSD	VGS=0V , IS=1A , TJ=25℃	---	---	1.2	V

Note :


1. The data tested by surface mounted on a 1 inch² FR-4 board with 2OZ copper.
2. The data tested by pulsed , pulse width $\leq 300\mu s$, duty cycle $\leq 2\%$
3. The EAS data shows Max. rating . The test condition is $V_{DD}=50V, V_{GS}=10V, L=0.5mH$
4. The power dissipation is limited by 150°C junction temperature




Typical Characteristics




Output Characteristics




Rdson-Junction Temperature




Transfer Characteristics




Gate Charge



Rdson- Drain Current




Source- Drain Diode Forward




Vds Drain-Source Voltage (V)

Capacitance vs Vds




T_C-Case Temperature (°C)

Power De-rating




Vds Drain-Source Voltage (V)

Safe Operation Area (Note 3)




T_C-Case Temperature (°C)

Current De-rating



Normalized Maximum Transient Thermal Impedance

TO-252-2L Package Information



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	2.200	2.400	0.087	0.094
A1	0.000	0.127	0.000	0.005
b	0.660	0.860	0.026	0.034
c	0.460	0.580	0.018	0.023
D	6.500	6.700	0.256	0.264
D1	5.100	5.460	0.201	0.215
D2	4.830 REF.		0.190 REF.	
E	6.000	6.200	0.236	0.244
e	2.186	2.386	0.086	0.094
L	9.800	10.400	0.386	0.409
L1	2.900 REF.		0.114 REF.	
L2	1.400	1.700	0.055	0.067
L3	1.600 REF.		0.063 REF.	
L4	0.600	1.000	0.024	0.039
ϕ	1.100	1.300	0.043	0.051
θ	0°	8°	0°	8°
h	0.000	0.300	0.000	0.012
V	5.350 REF.		0.211 REF.	