

Technical drawing of a 9-hole punch card. The card is rectangular with a width of 15 units and a height of 13.80 ± 0.20 units. The card is divided into 9 columns, numbered 1 to 9 from left to right. The columns are separated by vertical lines. The card has a 15-unit wide margin on the left and a 15-unit wide margin on the right. The card is labeled 'HSF' in a large, bold, sans-serif font in the top left corner. The card is labeled 'G' in the top right corner and 'G' in the bottom right corner. The card is labeled '15' in the bottom left corner. The card is labeled '13.80 ± 0.20' in the bottom center. The card is labeled '15' in the bottom right corner. The card is labeled 'G' in the bottom right corner. The card is labeled 'G' in the bottom right corner.

SPECIFICATIONS
Rated Current: 3AMP

The diagram shows a cross-section of a component with the following dimensions:

- Top layer thickness: 4.00 ± 0.15
- Distance from top layer to center: 3.73
- Distance from center to bottom layer: 2.00 ± 0.10
- Bottom layer thickness: $3.10 \pm 0.$
- Width of the central feature: A
- Width of the bottom layer: B

max. current: 50mA
Contact Resistance: 50mΩ Max



0.20

Withstand Voltage:1000VAC for 1 minute	
Insulation Resistance:1000MΩ Min	

Operation Temperature: -20°C to $+85^{\circ}\text{C}$

Un-mating force:0.49N	Min

0.17 ± 0.20

	Contact Plating: Au Over Ni	E

Housing Materials: PBT UL94V-0

20

