GlobTek, Inc.	Drawing Title: 3.1TYPE-C connector male 24P vertical three-legged without hook		
www.globtek.com	Model No. Connector		
186 Veterans Drive,			i
Northvale, NJ 07647			
Tel. (201) 784-1000	Part No./Ordering No. PLUG-USBC-241SMTV-4BQC13	Rev B1	
Fax (201) 784-0111			

In Addition to GlobTek Inc.'s renewed ISO9001:2008 - Quality Management System Certification, GlobTek Inc. is now certified to:

ISO13485:2003 - Medical Devices Quality Management System Certification ISO14001:2004 - Environmental Management System Certification

ISO Certificates are available online at <a href="http://www.globtek.com/iso-certificates/">http://www.globtek.com/iso-certificates/</a>

The acceptance of this specification and use of the product described in this document indicates the acceptance and binding of the customer to Globtek TERMS AND CONDITIONS (attached to the end of this document), which supersede all other agreements, terms, and conditions ( <a href="http://www.globtek.com/terms-and-conditions/">http://www.globtek.com/terms-and-conditions/</a>).

Prop 65 Statement: <a href="https://www.globtek.com/prop-65-statement.pdf">https://www.globtek.com/prop-65-statement.pdf</a>

### Footnote:

GlobTek Inc. will not be liable for the safety and performance of these power supplies if unauthorized access and repair occurs. End user should consult applicable UL, CSA or EN standards for proper installation instruction.

#### Limitation of Use:

GlobTek products are intended for use with commercial, medical, and/or industrial equipment only. GlobTek product are not authorized for use as mission critical components in life support hazardous environment, nuclear or aircraft applications without prior written approval from the CEO of GlobTek Inc.

Contents of this document are subject to change without prior notice.

Customer Approval of Specification:

Please approve, sign and send back to GlobTek so we can complete order processing.

A delay in receipt of this form will delay delivery schedule.

Company Name:	Customer P/N:
Quote Number:	Date:
Authorized Representative Name:	Authorized Representative Signature:

GlobTek, Inc.	Drawing Title: 3.1TYPE-C connector male 24P vertical three-legged without hook	
www.globtek.com	Model No. Connector	
186 Veterans Drive,		
Northvale, NJ 07647		
Tel. (201) 784-1000	Part No./Ordering No. PLUG-USBC-241SMTV-4BQC13	Rev B1
Fax (201) 784-0111		

## **REVISION HISTORY**

REV	DESCRIPTION	SUB	DATE	APPROVED
B1	Update the box quantity information	QA	06/20/2024	QA
В	Update drawing	QA	04/28/2023	QA
Α	Initial release	QA	07/20/2022	QA


## 3D CAD FILE:

#### https://www.globtek.com/file/dl/plug-usbc-241smtv-4bqc13.stp

## AGENCY ONLINE DOCUMENTS

RoHS/RoHS3 Declaration	https://www.globtek.com/pdf/rohs_cert/01t3a000005hQlhAAE		
REACH Declaration	https://www.globtek.com/r2/eM2co8		
Conflict Minerals Declaration	https://www.globtek.com/r2/SNw6P3		
Prop 65 Statement	https://www.globtek.com/r2/VMPRnr		

IPXY rating is based on 3rd party testing and customers should check suitability and test system level IPXY rating before ordering.



GlobTek, Inc.	Drawing Title: 3.1TYPE-C connector male 24P vertical three-legged without hook		
www.globtek.com	Model No. Connector		
186 Veterans Drive,			
Northvale, NJ 07647			
Tel. (201) 784-1000	Part No./Ordering No. PLUG-USBC-241SMTV-4BQC13	Rev B1	
Fax (201) 784-0111			

5	COVER	HIGH TEMPERATURE PLASTIC	LCP BLACK	1PCS
4	SPRING	STAINLESS STEEL		2PCS
3	LATCH	STAINLESS STEEL	TIN:80-120u"Min/Ni base:50u"Min Plated	1PCS
2	SHELL	STAINLESS STEEL	Ni:50u'Min Plated	1PCS
Ħ	TERMINALI HOUSING	HIGH TEMPERATURE PLASTIC	LCP BLACK/CONTACT:Au:1u*Min Ni base50u*Min	2PCS
NO.	DESCRIPTION	MATERIAL	REMARKS	QTY

A1	GND	B12	GND
A2	SSTXP1	B11	SSRXP1
A3	SSTXN1	B10	SSRXN1
A4	VBUS	B9	VBUS
A5	CC1	B8	SBU2
A6	DP1	B7	DN2
A7	DN1	В6	DP2
A8	SBU1	B5	CC2
A9	VBUS	B4	VBUS
A10	SSRXN2	В3	SSTXN2
A11	SSRXP2	B2	SSTXP2
A12	GND	B1	GND
PIN	SIGNAL NAME	PIN	SIGNAL NAME

## NOTES:

# SPECIFICATION:

1. CURRENT RATING: 3.0 MAX

2. VOLTAGE: 100VAC

3. TEMPERATURE RANGE: -30C ~ 85C


4. CONTACT RESISTANCE: 40MILLIONHM MAX

5. INSULATION RESISTANCE: 100 MEGA OHMS MIN.

6. INSERTION FORCE: 5N ~ 20N 7. UNMATING FORCE: 8N ~ 20N 8. DURABILITY: 10,000CYCLES

Temperature Life, Vibration, Cyclic Temperature and Humidity, Thermal Shock, Mixed Flowing Gas and etc.: https://www.globtek.com/pdf/ENVIRONMENTAL.pdf

GlobTek, Inc.	Drawing Title: 3.1TYPE-C connector male 24P vertical three-legged without hook	
www.globtek.com	Model No. Connector	
186 Veterans Drive,		
Northvale, NJ 07647		
Tel. (201) 784-1000	Part No./Ordering No. PLUG-USBC-241SMTV-4BQC13	Rev B1
Fax (201) 784-0111		



GlobTek, Inc.	Drawing Title: 3.1TYPE-C connector male 24P vertical three-legged without hook		
www.globtek.com	Model No. Connector		
186 Veterans Drive,			i
Northvale, NJ 07647			
Tel. (201) 784-1000	Part No./Ordering No. PLUG-USBC-241SMTV-4BQC13	Rev B1	
Fax (201) 784-0111			

PACKAGING				
Packing Spec P/N:				
Box Qty:	300			
Gift Box Size (mm):				
Gift Box Color:	White			
Master Carton Size (mm):	340 x 340 x 220			
Master Carton Cubic Volume	(m³): 0.03			
Master GW (Kg):	6.0 kg			
wt Ea. (Kg):	0.02 kg			
wt Ea. (Kg):	0.04 kg			
LABEL SPECS:,				
PACK SPEC:				