



Shenzhen Yajingxin Electron Co.,Ltd

Customer	
Production Name	SMD CRYSTAL GLASS 5.0*3.2
Customer P/N	N/A
P/N	T503224MLBDD1X
Revision	A
Print Date	2024-09-13

Drawn	Checked	Approved
		



RoHS Compliant




Shenzhen Yajingxin Electron Co.,Ltd

● ELECTRICAL PARAMETERS

谐振器产品技术指标		Min	Max	Units
1.Holder Type(型号规格)		GLASS 5.0*3.2 2PIN		
2.Mode of Oscillation (振动模式)		Fundamental		
3. Frequency (标称频率)		24.000000		MHz
4.Load Capacitance (CL) (负载电容)		20		pF
5.Drive Level (激励功率)		100		uw
6.Equivalent Resistance (谐振电阻)		≤30		Ω
7.Shunt Capacitance (Co) (静态电容)		0	7	pF
8.Motional Capacitance (C1) (动态电容)		N/A		fF
9.Frequency Tolerance at 25℃ (调整频差)		-10	10	ppm
10.Stability over operation temperance (温度频差)		± 20		ppm
11.Insulation Resistance (at DC 100V) (绝缘电阻)		≥500MΩ Min @100V		MΩ
12.Operating Temperature Range (工作温度范围)		-30	85	℃
13. Storage Temperature Range (储存温度范围)		-40	85	℃
14. Aging (老化率)		± 3		ppm/year
15. DLD2	N/A		N/A	Ω
16. FLD2			N/A	ppm
17. RLD2			N/A	Ω
18. SPDB	N/A		N/A	db
19. Other(其它)		N/A		

OUTLINE DIMENSIONS(UNIT:mm) 外形尺寸 (单位: mm)






Shenzhen Yajingxin Electron Co.,Ltd

● SUGGESTED REFLOW PROFILE (回流焊曲线图)


Total time:200sec.Max. (总时间: 200秒 最大)

Solder melting point:220℃ (熔点220 ℃)


Profiles Feature (特性)	Pb-Free Assembly
Average Ramp-up Rate(Ts max to Tp)平均升温速度	3℃/second Max
Preheat ■ Temperature Min (Ts min) 最低温度 ■ Temperature Max (Ts max) 最高温度 ■ Time (ts min to ts max) 从最低到最高时间	125℃ 200℃ (60~180) seconds
Time maintained above ■ Temperature(T1) 温度 ■ Time(tp) 时间	217℃ (60~150) seconds
Peak/Classification Temperature(Tp) 最高点温度	260 ℃
Time within 5℃ of actual Peak Temperature(tp) 高温维持时间	(20~40) seconds
Ramp-down rate 降温速度	6℃/second max
Time 25℃ to Peak Temperature 从25℃到最高温度的时间	8 minutes max
Suggest reflow times 建议 reflow次数	3 Times max



● PACKING (包装) 1Kpcs/REEL



SIZE	
A	1.7
B	5.45
C	3.65
D	8.0
E	12.0
IK	



REMARK :

1. 230 mm (9.05) minimum leader which consist of carrier and/or cover tape followed by a minimum of 160 mm (6.3) of empty carrier tape sealed with cover tape.
2. 160 mm (6.3) minimum trailer of empty carrier tape sealed with cover tape.