


# D6211A/B

## IR Filter Switch Driver

### General Description

D6211 is an IR filter switch driver IC designed for switching IR filter in IR-Cut Removable (ICR) of IP CAM. With appropriate input controls, D6211 functions as a one-channel, low saturation, bi-directional H-bridge driver. Built-in protection diode circuit can minimize the disturbance caused by the feedback current when the ICR is shut down, or when ESD impulse occurs.



The typical impedance of the current switches in D6211 shown in Fig. 1 is less than 3 ohms. The current driven through the actuator is then determined by the impedance of the ICR. For example, with 5.0V power supply, the current through the actuator is around 300mA with 0.73V output voltage drop.

Two types of D6211 (Ver. A & Ver. B) are offered to support single-wire control, dual-wire control and single-wire one-shot control modes as shown in Fig. Typical Application Circuit.

D6211 is offered in SOT-23-6L package.


### Features

- 1.8V input driving pulse
- Low saturation voltage (0.73V@300mA, VDD=5V)
- Low standby current (<10uA)
- 2.5V to 5.5V operating voltage range
- Only one control input and Built-in non-overlap circuit to avoid the MOSFET damage caused by the fast output voltage transient

### Applications

- IR filter switch driver for IR-Cut Removable (ICR) of IP CAM.

## Pin Configuration



## Pin Description

Pin No.	Symbol	I/O	Description
1	ENB/CE	I	Low-active enable/ External capacitor
2	GND	-	Ground
3	FBC	I	Forward/Backward control
4	OUT1	O	Driver output 1
5	VDD	-	Power supply
6	OUT2	O	Driver output 2

## Absolute Maximum Ratings (Tamb=25℃)

Parameter Name	Symbol	Rating	Unit
Supply Voltage	V <sub>DD</sub>	5.5	V
Input Voltage	V <sub>IN</sub>	V <sub>DD</sub> +0.4V	V
Output Current	I <sub>OUT</sub>	500	mA
Operating Temperature Range	Topr	-40~+125	℃
Storage Temperature Range	Tstg	-65~+50	℃

## Recommended Operating Conditions

Parameter Name	Symbol	Min	Typ	Max	Unit
Supply Voltage	V <sub>DD</sub>	2.5	5.0	5.5	V

## Electrical Characteristics ( $T_A=25^{\circ}\text{C}$ , $V_{DD}=5.0\text{V}$ unless otherwise noted)

Parameter Name	Symbol	Test Conditions	Min	Typ	Max	Unit
Supply Current	$I_{\text{STB(A)}}$	Steady state or standby state version A			20	$\mu\text{A}$
	$I_{\text{STB(B)}}$	Steady state or standby state version B			10	
	$I_{\text{DD}}$	Transit State	0.8	1.0	1.2	$\text{mA}$
<b>Driver Input Control ENB/FBC</b>						
Input High "H"	$V_{\text{IH}}$		1.6		$V_{\text{DD}}+0.4$	V
Input High "L"	$V_{\text{IL}}$		-0.4		$0.2 \cdot V_{\text{DD}}$	V
<b>Driver Output OUT1/OUT2</b>						
Output Voltage (upper+lower)	$V_{\text{OUT1}}$	$I_{\text{OUT}} = 200 \text{ mA}$		0.42		V
	$V_{\text{OUT2}}$	$I_{\text{OUT}} = 300 \text{ mA}$		0.73		V
	$V_{\text{OUT3}}$	$I_{\text{OUT}} = 400 \text{ mA}$		1.03		V
Rise Transition Time	$T_{\text{R}}$	From $0.1 \cdot V_{\text{DD}}$ to $0.9 \cdot V_{\text{DD}}$		2.5	5.0	ns
Fall Transition Time	$T_{\text{F}}$	From $0.9 \cdot V_{\text{DD}}$ to $0.1 \cdot V_{\text{DD}}$		3.5	7.0	ns
<b>Propagation Delay Time</b>						
ENB $\rightarrow$ OUT1 / 2 ("L" to "H")	$t_{\text{PLH}}$	$V_{\text{DD}} = 5\text{V}$ , Load= $18\Omega$		13	16	ns
ENB $\rightarrow$ OUT1 / 2 ("H" to "L")	$t_{\text{PHL}}$			36	43	ns
Pulse Width of ENB	$t_{\text{PW}}$		100			ns
Maximum Frequency of ENB	$T_{\text{MAX}}$				5	MHz

## Application Summary







Fig. Propagation delay time between ENB and OUT1/2





**Fig. PWM waveform for ENB**

## Typical Application



Input		Output	
ENB	FBC	OUT1	OUT2
H	X	L	L
L	H	H	L
L	L	L	H






The period of  $T_{\text{One-Shot}}$  is determined by the external capacitor connected on CE pin. It can be estimated from the equation.

$$T_{\text{One-Shot}} = 1.3 \times 10^6 \times C_{\text{CE}} \text{ (second)}$$

The time of one-shot would decrease 0.2 %/°C by temperature increase with the constant capacitance of  $C_{\text{CE}}$ . In fact, the capacitance of a real capacitor is affected by temperature change and has its maximum value at 25°C. It is suggested to set the time of one-shot more than twice time that the ICR-module needs.


The environment illumination can be detected by a photo sensor that is like CdS photo resistors or photodiodes. By using a comparator to decide day or night to control the direction of the FBC pin of D6211. Thus the IR lens position of the IR-cut module is according to the environment illumination. But a simple comparator circuit doesn't have any noise tolerance and there is too much glitch single due to the environment influence. A simple comparator circuit for a photo sensor is shown below. The resistor  $R_b$  is a bias resistor to generate the bias voltage for the photo sensor. The threshold voltage  $V_{\text{cmp}}$  that is decided by the resistors  $R_3$  and  $R_4$  is compared with the voltage of the photo sensor. The output direction of D6211 is according to the result of the comparator ( OP1 ).



The circuit is changed from a comparator to a schmitt trigger to solve the low noise tolerance issue. The offset voltage (  $V_{com}$  ) is generated by the resistors R3 and R4 and buffered by the buffer ( OP2 ). The threshold voltage (  $V_{cmp}$  ) can be expressed as


$$V_{cmp} = \frac{R2}{R1 + R2} (V_o - V_{com}) + V_{com} = \frac{R2}{R1 + R2} V_o + \frac{R1}{R1 + R2} V_{com}$$

Take the LMV358 for example, it is a rail-to-rail output operation amplifier. The output swing of LMV358 can be up to  $V_{cc}$  and down to GND. The high and low threshold voltage are expressed as



$$V_{cmp\_H} = \frac{R2}{R1+R2}V_{cc} + \frac{R1}{R1+R2}V_{com} \quad (V_o = V_{cc})$$

$$V_{cmp\_L} = \frac{R2}{R1+R2} \cdot 0 + \frac{R1}{R1+R2}V_{com} = \frac{R1}{R1+R2}V_{com} \quad (V_o = GND)$$




$$V_{th} = (V_{cmp\_H} + V_{cmp\_L})/2 = \frac{R2}{2(R1+R2)}V_{cc} + \frac{R1}{R1+R2}V_{com}$$

$$V_m = (V_{cmp\_H} - V_{cmp\_L})/2 = \frac{R2}{2(R1+R2)}V_{cc}$$

The new threshold voltage  $V_{th}$  and the noise margin  $V_m$  are shown above. These voltages can be got by choosing the properly resistance of  $R1$  and  $R2$ . The output of the schmitt trigger is changed when the variation of the photo sensor voltage is greater than  $2 \cdot V_m$ . This circuit has a great noise tolerance to avoid the disturbance of the environment influence.

## Outline Dimensions





## Statements

- Silicore Technology reserves the right to make changes without further notice to any products or specifications herein. Before customers place an order, customers need to confirm whether datasheet obtained is the latest version, and to verify the integrity of the relevant information.
- Failure or malfunction of any semiconductor products may occur under particular conditions, customers shall have obligation to comply with safety standards when customers use Silicore Technology products to do their system design and machine manufacturing, and take corresponding safety measures in order to avoid potential risk of failure that may cause personal injury or property damage.
- The product upgrades without end, Silicore Technology will wholeheartedly provide customers integrated circuits that have better performance and better quality.