


SOD-523

MARKING: C

特征 Features

- High Current Capability
- Low Forward Voltage Drop

机械数据 Mechanical Data






- SOD-523 Small Outline Plastic Package
- Polarity: Color band denotes cathode end
- Mounting Position: Any
- High temperature soldering guaranteed: 260°C/10s
- We declare that the material of product compliant with RoHS requirements and Halogen free

极限值和温度特性(TA = 25°C 除非另有规定)
Maximum Ratings & Thermal Characteristics (Ratings at 25°C ambient temperature unless otherwise specified.)

参数 Parameters	符号 Symbol	Limit	单位 Unit
峰值反向电压 Peak reverse voltage	VRM	30	V
直流反向电压 DC reverse voltage	VR	30	V
整理电流 Mean rectifying current	Io	0.2	A
峰值正向浪涌电流 8.3 ms single half sine-wave	IFSM	1.0	A
典型热阻 Typical thermal resistance	R _{θJA}	667	°C/W
功率消耗 Power Dissipation	PD	150	mW
存储温度 Storage temperature range	T _{STG}	-50-+150	°C

电特性 (TA = 25°C 除非另有规定)
Electrical Characteristics (Ratings at 25°C ambient temperature unless otherwise specified).

参数 Parameters	符号 Symbol	测试条件 Test conditions	Min	Typ	Max	单位 Unit
最大正向电压 Maximum forward voltage	V _F	IF = 10mA IF = 200mA			0.35 0.50	V
最大反向电压 Maximum reverse breakdown voltage	VR	IR=1mA	30			V
最大反向电流 Maximum reverse current	IR	VR=10V			30	uA

特性曲线Characteristic Curves

SOD-523 PACKAGE OUTLINE Plastic surface mounted package


Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.510	0.770	0.020	0.031
A1	0.500	0.700	0.020	0.028
b	0.250	0.380	0.010	0.015
c	0.080	0.150	0.003	0.006
D	0.750	0.850	0.030	0.033
E	1.100	1.300	0.043	0.051
E1	1.500	1.700	0.059	0.067
E2	0.200 REF		0.008 REF	
L	0.010	0.070	0.001	0.003
θ	7° REF		7° REF	

NOTICE

The information presented in this document is for reference only. Involving product optimization and productivity improvement, ChipNobo reserves the right to adjust product indicators and upgrade some technical parameters. ChipNobo is entitled to be exempted from liability for any delay or non-delivery of the information disclosure process that occurs.

本文件中提供的信息仅供参考。涉及产品优化和生产效率改善，ChipNobo 有权调整产品指标和部分技术参数的升级，所出现信息披露过程存在延后或者不能送达的情形，ChipNobo 有获免责权。

The product listed herein is designed to be used with residential and commercial equipment, and do not support sensitive items and specialized equipment in areas where sanctions do exist. ChipNobo Co., Ltd or anyone on its behalf, assumes no responsibility or liability for any damages resulting from improper use.

此处列出的产品旨在民用和商业设备上使用，不支持确有制裁地区的敏感项目和特殊设备，ChipNobo 有限公司或其代表，对因不当使用而造成的任何损害不承担任何责任。

For additional information, please visit our website <http://www.chipnobo.com>, or consult your nearest Chipnobo sales office for further assistance.

欲了解更多信息，请访问我们的网站 <http://www.chipnobo.com>，或咨询离您最近的 Chipnobo 销售办事处以获得进一步帮助。