

零件承认书

SPECIFICATION FOR APPROVAL

客户名称：001

增益型号：ZE6x10-651M-KJ

规格描述：DR6*10 0.2*167TS 脚长3.3±0.4 脚距5±0.3 L=650UH MIN穿套管 打K脚

日期：2024/6/11

版本：A

增益签核：

制订	审核	核准
夏琳		李万

客户签核：

工程	审核	核准



东莞市增益实业有限公司

地址：东莞市塘厦镇林村塘厦大道北552号

电话：0769-87321000

传真：0769-87891229

物料类型：

工字电感

日期：

2024/6/11

版本：

A




产品承认书

SPECIFICATION FOR APPROVAL


客户名称 CUSTOMER		日期 DATE	2024-09-30
客户物料编号 CUSTOMER P/N		客户规格型号 DESCRIPTION	DR6*10 0.2*167TS 脚长 3.3±0.4 脚距5±0.3 L=650UH MIN穿套管 打K脚
我司物料编号 OUR PART NO		我司品名 OUR PART NAME	立式工字电感

外观尺寸 Appearance of size
单位 Unit: mm



A	7.5 MAX	C	0.6±0.1	E	5.0±0.5		
B	12.5 MAX	D	3.3±0.5	F	3.0±1.0		
标识Identification							

原理图 Schematic Diagram



绕线结构表 Winding Structure Diagram

绕组 WINDING	起始 S	结束 F	漆包线 WIRE	圈数 TURNS		绕制方式 WINDINGWAY		
N1	S	F	2UEW-0.2mm	167.5TS	圈数参考	平整密绕		

注意事项 Matters needing attention:



产品承认书

SPECIFICATION FOR APPROVAL

客户名称 CUSTOMER		日期 DATE	2024-09-30
客户物料编号 CUSTOMER P/N		客户规格型号 DESCRIPTION	DR6*10 0.2*167TS 脚长3.3±0.4 脚距5±0.3 L=650UH MIN穿套管 打K脚
我司物料编号 OUR PART NO		我司品名 OUR PART NAME	立式工字电感
电性参数 Electrical parameters			
测试项目 TEST PROJECT	电性范围 SPEC	测试条件 TEST FREQ	测试仪器 TEST STRUMENTS
电感量L	650UH min	at 25℃ 1KHz/0.25V	TH2812D
直流电阻DCR	2.5Ω MAX	at 25℃ 1KHz/0.25V	TH2812D
饱和电流Isat	L ≥ L0*90%	at 25℃ DC250mA 1KHz/0.25V	TH2829A
物料清单 BOM			
物料 MATERIAL	规格型号 SPECIFICATIONS	制造厂商 MANUFACTURERS	UL证书号 UL FILE NO
EPOXY RESIN	FK661	QI FU	
		OR Equivalent supplier	
WIRE	2UEW-F(QA)		E233255
		OR Equivalent supplier	
SOLDER	Sn:99.3%/Cu:0.7%	SONGBEN	
		OR Equivalent supplier	
TUBE	UL HEAT-SHRINKABLE TUBE/125℃	XINGQI	E350991
		OR Equivalent supplier	
PIN	Tinned copper clad steel wire	BAICHUAN	
		OR Equivalent supplier	
CORE	MgZn DR2W6*10	LIANXING	
		OR Equivalent supplier	



产品承认书
SPECIFICATION FOR APPROVAL

客户名称 CUSTOMER		日期 DATE	2024-09-30
客户物料编号 CUSTOMER P/N		客户规格型号 DESCRIPTION	DR6*10 0.2*167TS 脚长3.3±0.4 脚距5±0.3 L=650UH MIN穿套 管 打K脚
我司物料编号 OUR PART NO		我司品名 OUR PART NAME	立式工字电感

测试报告 The test report

测试项目 Test project	电性范围 Spec	测试数据 Test data				
		1	2	3	4	5
电感量L	650UH min	706	704	695	698	701
直流电阻DCR	2.5Ω MAX	1.35	1.38	1.36	1.35	1.37
饱和电流Isat	L≥L0*90%	OK	OK	OK	OK	OK

测试室温/湿度： 室温: 25℃(REF) 相对湿度: 80%(REF)
TEST CONDITIONTEMP:25℃(REF) R.H.: 80%(REF)

序号	项目	技术要求	结论
1	外观和尺寸	符合产品规范和公差要求	OK
2	引脚拉脱力	大于等于1Kg	OK
3			

制表 MADE	审核 CHECKED	批准 APPROVED
黄禾香	饶平	钟翠兰



注意事项

Matters needing attention

1、本公司产品适用于 AV 设备、OA 设备、家电、信息服务等一般电子设备中。

Our products are designed and promoted for use in general electronic devices such as audio-video equipment, office automation equipment, home appliance and information service.

2、当本公司的产品使用在一般电子设备以外的领域时，对于此所引发的设备失效我司将不承担任何法律责任。

In case of using the product for the purpose other than general electronics devices, we shall not be held liable for any dysfunctions in or damage to the equipment with which the product is used.

3、本承认书只保证我司产品作为一个单体时的质量情况，当我司产品被安装到贵司产品上时，请贵司对使用在贵司电路上的产品情况进行了有效评价和确认。

Our specification limits the quality of the component as a single unit. Please ensure the component is thoroughly evaluated in your application circuit.

4、不要对产品施加过大的振动或机械冲击；

Do not apply excessive vibration or mechanical shock to products.

5、为防止断线，请不要使用锋利的物体接触线圈，如镊子；

Do not touch wire with sharp objects such as tweezers to prevent wire breakage.

6、在产品贴装时不要使用过大的压力，避免磁芯断裂。

Do not apply excessive stress to products mounted on boards to prevent core breakage.

7、为保证端子电极的焊接特性和包装材料处于良好状态，请于本公司发货后 6 个月内使用本产品。同时，由于端子电极的焊接特性会随时间发生变化，如果贮存时间超过 6 个月，请首先确认其焊接特性后再安装使用。

To maintain the solderability of terminal electrodes and to keep the packing material in good condition, product should be used within 6 months from the time of delivery. And the solderability of products electrodes may decrease as time passes, so in case of storage over 6 months, solderability shall be checked before actual usage.

8、存放货物的仓库应满足以下条件 Store products in a warehouse in compliance with the following condition:

条件 Conditions	元件含包装物 Packing status	元件自身 Component itself
温度 Temperature	-25~+40℃	-25~+85℃
湿度 Humidity	30~70%RH	30~70%RH

9、不要使产品遭受温度和湿度的快速变化。

Do not subject products to rapid changes in temperature and humidity.

10、不要将产品存放在化学环境中，如硫酸气体或碱性气体中，否则会降低电极端子的焊接特性和使电感器腐蚀。

Do not store the products in chemical atmosphere such as one containing sulfurous acid gas or alkaline gas, that will causes poor solderability and corrosion of inductors.

11、为了避免受潮气、灰尘等物质的影响，产品应保管于货架上。

Store products on pallets to protect from humidity, dust, etc

12、产品应避免热冲击、振动以及直接光照等等。

Avoid heat shock, vibration, direct sunlight, etc.